

Reliable, easy, cost effective video transmission over phonelines is available today!



front view

SVTU (Smart Video Transmission Unit)

'The Professional Solution'

interior view

SVTU (Smart Video Transmission Unit)

models feature...

UNIT

- Unit measures 12" x 11" x 3" weighs less than 5lbs
- Power Requirements 12VDC filtered 1 AMP min (not included)
- Simple to Install
- Settings may be programmed remotely

VIDEO

- Up to 12 video sources
- Loop Through for all video inputs
- Monitor output with sequencing switcher
- Video includes SITE ID and time stamp
- Pre-alarm recording for all cameras
- Built in video switcher
- Video transmission at up to 15 FPS (frames per second) over PSTN lines

ALARM INPUTS

- Up to 16 Alarm Trigger Inputs
- May be associated with any alarm zone (camera)
- Programmable to normally open, normally closed or transient trigger
- 24 hour activated or activated only when system is armed
- Delayed or instant action
- Automatic Transmission or on-site recording
- Record pre and or post-alarm video from a selected zone

AUDIO

- Audio inputs
- Simultaneous video and optional two way audio transmission, over standard phones lines

COMMUNICATION

- Built-in modem
- Built in RS-232 port allows connection of ISDN lines
- Supports PSTN, ISDN & cellular (GSM & CDMA)
- Shared line access features allow the unit to be connected to a FAX or answering machine and still operate the Smart Video Transmission Unit

ADDITIONAL SECURITY

- Control external devices such as lights, doors and sounders
- Built-in backup power supply (battery not included)
- Internal Tamper Switch
- Self-Test on all major functions and ports
- Control P,T,Z (pan/tilt/zoom) of cameras

RECEIVING SIDE

- Control Center software Included; plug-n-play; icon driven interface compatible with Windows 95/98/NT/2000/Me/XP
- Optional Windows CE compatible software is available for PDAs and other remote devices

all units ship with

Transmission unit
Users Manual
Control Center Software
(Updates available)
Software Users Manual

Color units

Ozline 12VC

10-12VC2

12 Channel wall mount COLOR VIDEO transmission unit

(12 inputs 1 output)

10 Frame pre and post alarm storage on a pre selected camera.

Ozline 12VC_{DRAM}

10-12VC2_{DRAM}

12 Channel wall mount COLOR VIDEO transmission unit

(12 inputs 1 output)

Memory enhanced with an additional 8Mb D-RAM storage enables local video capture of 1000 frames for auto or manual download, Pre and post alarm storage on all cameras.

Monochrome unit

Ozline 12VM

10-12VM2

12 Channel wall mount MONOCHROME VIDEO transmission unit

(12 inputs 1 output)

10 Frame pre and post alarm storage on a pre selected camera.

Accessories

Ozline-REX

10-REX

Form 'C' Relay Expansion Board. Expands 3 standard outputs into 12 activation outputs for remote control of devices.
Contact Rating Maximum 100MA@24VDC

1-800-385-2317



1-781-581-8254

Ozline gives you tomorrow's technology...today
www.ozvisionamerica.com

Top